



HANNA RUBBER COMPANY

Specification Sheet

STANDARD HEATER HOSE

Engineered with superior flexibility and durability, Flexfab's standard heater hose is resistant to coolant additives, as well as hardening, cracking, cold leaks, and aging. It's extreme duty cycle tested.

CONSTRUCTION:

- + Silicone hose with 1-ply of nylon fiber reinforcement
- + Available in:
- + Stocked in 25' and 50' boxes
- + Available in longer lengths on standard wooden spools*
 - *Continuous lengths are not guaranteed, if continuous lengths are required please contact a sales rep for price and availability

SPECIFICATIONS:

- + Meets or exceeds the operating requirements of SAE J20 R3 Class A
- + Meets or exceeds the operating requirements of TMC RP303B Class I Grade II
- + Standard wall thickness is .140"/.170"
- + Working pressure is 1/3 of the burst pressure
- + Bend radius is 5 times the ID of the hose
- + Resists hardening, cracking, cold leaks, aging, and many chemicals


BENEFITS

- ✓ Box and Spool Lengths Available
- ✓ Extreme Temperature Resistance
- ✓ Superior Flexibility
- ✓ Extreme Duty Cycle Tested for Hostile Engine Environments
- ✓ Durable Construction
- ✓ Resistant to Coolant Additives

CUSTOM ENGINEERED TO WITHSTAND:



TEMPERATURE RANGE:





HANNA RUBBER COMPANY

Specification Sheet

STANDARD HEATER HOSE

Inside Diameter		Outside Diameter		Actual Burst Pressure - PSI	Burst Pressure - PSI		Weight (LB/FT)	Overall Length (Feet)
Inch	MM	Inch	MM		SAE J20 R1	TMC		
0.25	6	0.58	5	320	2.0	25	0	25 Box
0.25	6	0.58	5	320	2.0	25	0	50 Box
0.25	6	0.58	5	320	2.0	25	0	250 S 00
0.25	6	0.58	5	320	2.0	25	0	800 S 00
0.3	8	0.64	6	3.0	250	25	0.28	25 Box
0.3	8	0.64	6	3.0	250	25	0.28	50 Box
0.3	8	0.64	6	3.0	250	25	0.28	600 S 00
0.38	0	0.7	8	3.0	250	25	0.45	25 Box
0.38	0	0.7	8	3.0	250	25	0.45	50 Box
0.38	0	0.7	8	3.0	250	25	0.45	250 S 00
0.38	0	0.7	8	3.0	250	25	0.45	600 S 00
0.50	3	0.83	2	3.0	250	25	0.8	25 Box
0.50	3	0.83	2	3.0	250	25	0.8	50 Box
0.50	3	0.83	2	3.0	250	25	0.8	250 S 00
0.50	3	0.83	2	3.0	250	25	0.8	00 S 00
0.63	6	0.96	24	300	250	25	0.26	25 Box
0.63	6	0.96	24	300	250	25	0.26	50 Box
0.63	6	0.96	24	300	250	25	0.26	250 S 00
0.63	6	0.96	24	300	250	25	0.26	400 S 00
0.75	9	0.8	27	300	200	25	0.25	25 Box
0.75	9	0.8	27	300	200	25	0.25	50 Box
0.75	9	0.8	27	300	200	25	0.25	250 S 00
0.75	9	0.8	27	300	200	25	0.25	300 S 00
0.88	22	2	3	250	75	25	0.287	25 Box
0.88	22	2	3	250	75	25	0.287	50 Box
0.88	22	2	3	250	75	25	0.287	200 S 00
00	25	33	34	250	75	25	0.324	25 Box
00	25	33	34	250	75	25	0.324	50 Box
00	25	33	34	250	75	25	0.324	200 S 00
25	32	58	40	200	75	25	0.385	25 Box
25	32	58	40	200	75	25	0.385	50 Box
25	32	58	40	200	75	25	0.385	50 S 00